

SLIPRING Type PSP 20 - 60 A

TECHNICAL SHEET 3.4



MAIN PERFORMANCES

- HOUSING: Metallic
- POSITIONING: Vertical axis with 2 fixed screws M10
- CABLE ENTRY: Through central hole for terminal box and through two pipes union 3/4" Gas for the brush holders
- BRUSHES: 20 A and 60 A in copper graphite. Slideway between rings and brushes secured by a "V" special contact
- EXECUTIONS: From 18 to 36 rings 20 A - mixed executios 20/60 A
- ARMONIZED RULES: EN 60947-5-1 EN 60529
EEC 73/23 - EEC 89/336 - EEC 89/392 Directive
- MARKING: CE

ELECTRICAL FEATURES

- NOMINAL VOLTAGE: 660 V AC - DC
- NOMINAL CURRENT: Ith 20 - 60 A
- PROTECTION DEGREE: IP 42
- MAX ROTATING SPEED: 30 revs/min.
- TEST VOLTAGE: 2,5 kV
- OPERATING TEMPERATURE: -20 °C ÷ +60 °C

STANDARD TYPES

H = mm	Single	Mixed		TOT.
	20 A N ° rings	60 A	30 A N ° rings	
270	18	4	10	14
315	24	4	16	20
360	30	4	22	26
415	36	4	28	32

DIMENSIONS

